

Hot Stamping Foil – MAM Series

Product Data Sheet

Foil Specifications

Polyester Film Thickness:	12µm (0.012mm)
Standard Width:	25" (64cm)
Standard Length(s):	200' (61m); 400' (122m); 1000' (305m); 2000' (610m); 3000' (914m); 4000' (1219m)
Custom Widths and Lengths:	Available upon request

Stamping Effects

Release:	Stamps, difficult applications and troublesome surfaces like UV coatings or film laminations
Detail:	Fine Line to Medium Broad
Appearance:	Metallic
Overstamp with Foil:	Yes, dependent on image and other hot stamping foils
Overprint with Inks and Varnishes:	Yes, dependent on inks, image and paper used

Product Performance

Abrasion Resistance:	Good adhesion, abrasion and scratch resistance
Adhesion Characteristics:	Excellent with UV coatings or film laminations with low dyne levels
Running Temperature:	Sheetfed 225–275°F / 107–135°C Rotary 265–320°F / 129–160°C

Storage and Shelf Life Requirements

Two (2) years in dry, climate-controlled conditions and stored on its end, not on side

Industries Served

Greeting Card, Packaging, Commercial Printing

Product Application

Labels (including PL, PET, polypropylene), Printed Papers, Packaging and Film Laminates