

## Sheetfed Cold Stamping Foil – MCOF Grade

### Product Data Sheet

#### Foil Specifications

---

<b>Polyester Film Thickness:</b>	12µm (0.012mm)
<b>Standard Width:</b>	25" (64cm), 40" (101.6cm), 50" (128cm)
<b>Standard Length(s):</b>	10,000' (3048m); 26,000' (7825m) on 3" or 6" cores
<b>Custom Widths and Lengths:</b>	Available upon request

#### Stamping Effects

---

<b>Use:</b>	Special purpose foil for sheetfed cold foiling
<b>Applications:</b>	Can be used on a wide range of coated papers, label stock, and plastic films
<b>Press Needs:</b>	Can be used on suitably modified sheetfed printing machines with cold-foiling capabilities
<b>Release:</b>	Very easy
<b>Detail:</b>	Fine to heavy
<b>Appearance:</b>	Metallic
<b>Effects:</b>	Good halftone effects
<b>Overprint with Inks and Varnishes:</b>	Yes, dependent on inks, image and paper used

#### Product Performance

---

<b>Abrasion Resistance:</b>	Good abrasion and scratch resistance
<b>Adhesion Characteristics:</b>	Adheres to specially formulated adhesive which has been "printed" on the substrate Use an appropriate adhesive Adjust adhesive lay-down to suit the substrate
<b>Running Speed:</b>	10–18m/min. (Higher speeds are very dependent on the substrate and design)

#### Storage and Shelf Life Requirements

---

Two (2) years in dry, climate-controlled conditions and stored on its end, not on side

#### Industries Served

---

Packaging, Commercial Printing

#### Product Application

---

Printed Papers and Packaging