

9090 Nieman Road • Overland Park, KS 66214 • (913) 888-7340 • Toll Free: 877-932-3645 • info@infinityfoils.com • infinityfoils.com

Hot Stamping Foil - MIO Series

Product Data Sheet

Foil Specifications

Polyester Film Thickness: 12µm (0.012mm)

Standard Width: 25" (64cm); 50" (128cm)

Standard Length(s): 200' (61m); 400' (122m); 1000' (305m); 2000' (610m);

3000' (914m); 4000' (1219m)

Custom Widths and Lengths: Available upon request

Stamping Effects

Release: Easy

Detail: Fine to Medium

Appearance: Metallic

Overstamp with Foil: Yes, well-suited for overstamping applications; dependent on

image and other hot stamping foil

Overprint with Inks and Varnishes: Yes, dependent on inks, image and paper used

Product Performance

Abrasion Resistance: Good abrasion and scratch resistance

Adhesion Characteristics: Good adhesion

Running Temperature: Sheetfed 212 – 266°F / 100 – 130°C

Cylinder 266 – 320°F / 130 – 160°C **Rotary** 260 – 320°F / 127– 160°C

Storage and Shelf Life Requirements

Two (2) years in dry, climate-controlled conditions

and stored on its end, not on side

Industries Served

Rotary, Greeting Cards, Packaging, Commercial Printing,

PET/OPP films

Product Application

Wine Labels, Cosmetics Labels, Packaging/Labels